



small diamond groove with bonding layer




large diamond groove with bonding layer

Wear resistant drum lagging made of rubber, plain or profiled, with or without adhesive layer in different qualities.

**THE GROOVED
PULLEY LAGGING**

- Pulley lining for increasing of the friction value between conveyor belt and pulley
- minimizing of the belt slip, and improvement of self-cleaning.
- protection of the pulley to prevent wearing off and corrosion
- Prevents material build-up



Diamond grooves

	Height A	Width B	Distance C	Depth
small	17 mm	33 mm	6 mm	3 mm
large	51 mm	88 mm	6 mm	4 mm

	HARDNESS DIN 53505	ABRASION DIN 53516	ELASTICITY DIN 53512	COLOUR
ANB	60±5 Sh° A	120mm ³	30%	BLACK

THICKNESS	WIDTH	LENGTH	BONDING LAYER	ITEMS
8 mm	2.000 mm	10.000 mm	BONDING LAYER	ANB 08/BL
10 mm				ANB 10/BL
12 mm				ANB 12/BL
15 mm				ANB 15/BL

THICKNESS	WIDTH	LENGTH	WITHOUT BONDING LAYER	ITEMS
8 mm	2.000 mm	10.000 mm	WITHOUT BONDING LAYER	ANB 08
10 mm				ANB 10
12 mm				ANB 12
15 mm				ANB 15